
"APPROVED FOR RELEASE: 06/12/2000 CIA-RDP86-00513R000308210014-2



"APPROVED FOR RELEASE: 06/12/2000

CIA-RDP86-00513R000308210014-2

sov/81-59-21-73780

Translation from: Referativnyy zhurnal, Khimiya, 1959, Nr 21, p 7 (USSR)

AUTHORS:

Kaliteyevskiy, N.I., Chayka, M.P.

,0, 10

TITLE:

The Ratio of Magnetic and Quadruple Moments of U233 and U235 Nuclei

PERIODICAL:

Fiz. sb. L'vovsk. un-t, 1958, Nr 4(9), pp 12 - 14

ABSTRACT:

In continuation of the work published earlier (RZhKhim, 1957, Nr 16, 53621) spectroscopic evaluations have been made of the ratio of the magnetic moments of U232 and U235 under the assumption that the spin of both uranium isotopes is equal to 7/2. The ratio of the magnetic moments is equal to 1.6 ± 0.1 A and that of the quadrupole moments to 0.8 ± 0.3 .

S. Shushurin



Card 1/1

KALITEYEVSKIY, N.I. CHAYKA, N.P.

Spectroscopic determination of nuclear moments of Cu⁶³ and Cu⁶⁵. Fix. sbor. no.4:21-24 *58. (MIRA 12:5)

1. Leningradskiy ordena Lenina gosudarstvennyy universitet imeni A.A. Zhdanova. (Copper--Isotopes) (Nuclear moments)

ZAYDEL', A.N.; KALITHYEVSKIY, N.I.; LIPIS, L.V.; CHAYKA, M.P.

Spectrum analysis of thorium and beryllium by the vacuum evaporation method. Fig. sbor. no.4:31-32 158. (NIRA 12:5)

l. Fisicheskiy institut Leningradskogo ordena Lenina gosudarstvennogo universiteta imeni A.A.Zhdanova. (Thorium-Spectra) (Beryllium-Spectra)

Kaliteyevskiy, N. I., Perel', V. I.,

sov/48-22-6-14/28

AUTHORS:

TITLE:

Chayka, M. P. On the Accuracy of the Determination of Constants of the Hyperfine Structure From Optical Measurements (O tochnosti opredeleniya konstant sverkhtonkov struktury iz opticheskikh izmereniy)

PERIODICAL:

Izwestiya Akademii nauk SSSR, Seriya fizicheskaya, 1958, Vol. 22, Nr 6, pp. 692-695 (USSR)

ABSTRACT:

In the introduction it is pointed out that this problem has not found the attention it deserves in publications in spite of its great importance which is due to the fact that knowledge of the constants of hyperfine structure makes it possible, without quantum-mechanical calculation to determine important nuclear constants as e.g. the relation of the magnetic and quadrupole moments of two isotopes of an element. The theories relating to this problem are discussed (Refs 1-8). In this connection it was found that the results obtained for the constants of hyperfine structure obtained by various methods show satisfactory agreement with respect to magnetic nuclear moments, but that, with respect to quadrupole moments these values (B) differ by up to the

Card 1/2

On the Accuracy of the Determination of Constants of the Hyperfine Structure From Optical Measurements

SOV/48-22-6-14/28

1.5-fold. Therefore the conclusion is drawn that the accuracy of optical measurements when determining moments of higher order (e.g. octupoles) are unreliable. By way of an example it is mentioned that the value computed in this paper for A₂ for the term D₂/2 for copper apparently does not represent octupole interaction but must be considered to be caused by systematic errors in measuring the position of sublevels of hyperfine structures. There are 1 table and 9 references, 3 of which are Soviet.

ASSCULATION:

Fizicheskiy institut Leningradskogo gos. universiteta im. A. A. Zhdanova (Institute of Physics, Leningrad State University imeni A. A. Zhdanov)

- 1. Materials—Structural analysis 2. Materials—Optical analysis
- 3. Structural analysis -- Effectiveness

Card 2/2

24(7) AUTHORS:

Kaliteyevskiy, N. I., Chayka, M. P.

SOV/54-59-3-10/21

TITLE:

Photoelectric Measurement of the Relative Intensities of the Hyperfine Structural Components With the Problem of Spin

Determination of the Lu 176 Nucleus

PERIODICAL:

Vestnik Leningradskogo universiteta. Seriya fiziki i khimii,

1959, Nr 3, pp 51-60 (USSR)

ABSTRACT:

In the present paper the hyperfine structure of Lu¹⁷⁶ is investigated and herefrom the nuclear spin is determined. It was found that for obtaining sufficiently precise data an enrichment of Lu¹⁷⁶ to 30% is necessary. The line Lu II λ 6463 λ (${}^{3}P_{0}-{}^{3}D_{I}$)

(Fig 1) was measured. The spectrometer (Fig 2) is described; it consists mainly of a Fabri-Perot interferometer of the type IZS-9. The metallic mirror had multi-layered dielectric coatings produced by T. N. Krylova scientific collaborator of the GOI. A circular stop was used for centering and increasing the light intensity. A diffraction monochromator was used to separate the lines to be investigated. This grating was capable of centering up to 50% of the required line. An additional filter was used

Card 1/3

Photoelectric Measurement of the Relative Intensities SOV/54-59-3-10/21 of the Hyperfine Structural Components With the Problem of Spin Determination of the Lu¹⁷⁶ Nucleus

to eliminate superpositions. The light (emerging) from the spectrometer hits a photomultiplier the signals of which were collected by a bridge scheme. The light intensity of the apparatus, as one of the most important elements, was determined. In this connection the contribution of each individual part of the instrument was taken into account. For the excitation of the lines a gas discharge tube was used with a liquid air cathode. From a series of pictures of natural Lu the spin of Lu^{175} to I = 7/2 was determined from the relative intensities of the components. The separation of the background and the elimination of superpositions as well as a consideration of the changes of the cathodes was made. Tables 1 and 2 show the relative intensities of the two components and a comparison with the theoretical value. The measured value of c/a is 1.31 \pm 0.03. The theoretical mean value is found at $c/a = 1.308 \pm 0.012$. Herefrom the nuclear spin I = 7 was determined. The next possible values I = 6 and I = 8 are still

Card 2/3

Photoelectric Measurement of the Relative Intensities SOV/54-59-3-10/21 of the Hyperfine Structural Components With the Problem of Spin Determination of the Lu¹⁷⁶ Nucleus

within the error limit. These values are in good agreement with the results obtained by Gallagher and Moszkowski (Ref 9) and Peker (Ref 10). In conclusion, the authors thank S. E. Frish for his interest in the work, V. S. Zolotarev for the production of the enriched preparation, G. K. Yeremin for having supplied natural lutecium, and L. K. Peker for the discussion of the results obtained. There are 5 figures, 2 tables, and 11 references, 5 of which are Soviet.

SUBMITTED:

April 15, 1959

Card 3/3

SOV/51-6-6-26/34

24(7), 24(4)

Kaliteyevskiy, N.I., Malyshev, G.M. and Chayka, M.P.

AUTHORS:

A Photoelectric Spectrometer with a Fabry-Perot Interferometer (Fotoelektricheskly spektrometr s interferometrom fabri-pero)

PERIODICAL: Optika i spektroskopiya, 1959, Vol 6, Nr 6, pp 820-822 (USSR)

ABSTRACT:

Jacquinot (Ref 1), Chabbal (Ref 2) and Chayka (Ref 3) showed that the speed of a spectrometer with a Fabry-Perot interferometer is much higher than the speed of a similar spectrometer with a diffraction grating. The present paper discusses a photoelectric spectrometer developed at NIFI of the Leningrad State University (Fig 1). High resolving power of the instrument was ensured by a Fabry-Perot interferometer (2 in Fig 1) with dielectric reflecting coatings. 7-layer coatings of TiO2 and SiO2 were deposited chamically on this interferometer in T.N. Krylova's laboratory. The interferometer was placed into a hermetically sealed chamber in which the pressure could be varied from several mm Hg to one atmosphere. The uniformity of the scanning rate was ensured by supplying nitrogen from a high-pressure cylinder (~100 atm) through a narrow capillary 6 to the interferometer chamber. Interference rings were focused in the plane of the slit of a diffraction monochromator &. A circular diaphragm 1 was used to separate out the required portion of the central interference ring. A diffraction spectrum of the 7th

card 1/2

A Photoelectric Spectrometer with a Fabry-Perot Interferometer

SOV/51-6-6-26/34

order was used in the green region and the 5th order was used in the red region. High angular dispersion of the instrument made it possible to use wide slits and this ensured high speed of the apparatus. To avoid transposition of the diffraction-spectrum orders another monochromator (3) with a constant deviation angle was used between the source of light (4) and the interferometer (2). The light signal from the diffraction monochromator (8) was recorded by means of the photomultiplier, d.c. amplifier and a recording potentiometer EPP-09. Four types of photomultipliers were used: FEU-17 in the blue and green regions, FEU-12 and FEU-14 in the yellow and red regions and FEU-22 for wavelengths longer than 6600 A. The apparatus described was used to record the hyperfine structure of lines of certain isotopes of lutecium, gadolinium and holmium. Fig 2 shows the record of the hyperfine structure of the holmium line at 5982 A. A hollow-cathede discharge tube was used as the source of light. There are 2 figures and 6 references, 4 of which are Soviet and 2 French.

Card 2/2

"APPROVED FOR RELEASE: 06/12/2000 CIA-RDP86-00513R000308210014-2

KALITEYEVSKIY, N.I.; CHAYKA, M.P.

Photoelectric measurements of relative intensities of components of hyperfine structure for the determination of the spin of the Iul 176 nucleus. Vest.LGU 14 no.16:51-60 159. (MIRA 12:10) (Intetium)

21 (1) A=Th>RS:

Kaliteyevskiy, N. I., Chayka M. P. SOV/56-37-3-57/62

Pacheva, I. Kh., Fradkin, E. Ye.

TITLE:

Nuclear Moments of the Odd Gadolinium Isotopes

PERIODICAL:

Zhurnal eksperimental noy i teoreticheskoy fiziki, 1959, Vol 37,

Nr 3(9), pp 882 - 884 (USSR)

ABSTRACT:

The present "Letter to the Editor" contains an abundance of details partly taken from the authors' own investigations and partly from other publications. In an earlier paper (Ref 1) the hyperfine structure of the 3 lines of Gd I: 5015, 5103, and 5251 I was investigated by means of a photoelectric spectrometer. The investigations were carried out on the very pure iso-

topes $Gd^{155}(97.3\%)$ and $Gd^{157}(91.4\%)$. Both isotopes have the spin I = 3/2. The magnetic moments: $\mu_{155} = -0.32\pm0.04$,

 $\mu_{157} = -0.40\pm0.04$. The quadrupole moments: $Q_{155} = 1.6\cdot10^{-24}$ cm², $Q_{157} = 2\cdot10^{-24}$ cm²; these values are nearly double as high as

those found by Speck. The internal quadrupole moments

 $q_{155}^{155} = 6 \cdot 10^{-24} \text{cm}^2$ and $q_{157}^{157} = 10 \cdot 10^{-24} \text{cm}^2$ agree as to the order

Card 1/2

Nuclear Moments of the Odd Gadolinium Isotopes

SOV/56-37-3-57/62

of magnitude with those obtained according to the method of the Coulomb excitation of the gadolinium nuclei. The deformation parameters were found to amount to $\delta_{155}=0.31$ and $\delta_{157}=0.37$. With respect to the gyromagnetic ratios g_K and g_R (of the internal and collective motions) data, which were obtained from Nilsson's tables, are compared with those obtained by other (Western) authors. Calculations resulted in $g_K = 0.8$ nuclear magnetons and $g_K = 0.9$ nuclear magnetons, $g_R = 0.9$ nuclear magnetons, $g_R = 0.7$. The data concerning the $g_K = 0.9$ are finally compared with those obtained by Gauvin. The authors thank V. S. Zolotarev for placing the isotopes at their disposal, and L. K. Peker for his advice and discussions. There are 9 references, 2 of which are Soviet.


ASSOCIATION:

Fizicheskiy institut Leningradskogo gosudarstvennogo universiteta (Institute of Physics of Leningrad State University)

SUBMITTED:

June 19, 1959

Card 2/2



21(1) MITHORS: Kaliteyevskiy, N. I., Chayka, M. P.

SOV/20-126-1-14/62

TITLE:

Spectroscopic Determination of the Lu 176 Nuclear Spin (Spektroskopicheskoye opredeleniye spina yadra Lu 176)

PERIODICAL:

Doklady Akademii nauk SSSR, 1959, Vol 126, Nr 1, pp 57-58 (USSR)

ABSTRACT:

The spin of the In 176 nucleus is determined by the relative intensity of the components of the hyperfine structure of the line In 11 \(\lambda \) (3P_3D_1). The scheme of the structure of this line is shown in figure 1. According to the amount of spin of the In 176 nucleus, the ratio of intensities of the two extreme components (c/a) must assume the following values:

8

1308 1267 1444 1364 Accurate optical measurements are disturbed by the components of

the fine structure of In 175, but by the choice of a suitable Fabry-Perot interferometer, the 3 components of In 175 and the

Card 1/3

Spectroscopic Determination of the Lu¹⁷⁶ Nuclear Spin

307/20-126-1-14/62

central component of Lu 176 can be put into agreement. The measurements were made by means of a photoelectric spectrometer with an Fabry-Perot interferometer. The spectrum of the lutecium was excited in a gas discharge tube with a hollow cathode cooled by liquid air. To eliminate possible systematic errors, the hyperfine structure of the line of Lul75 was recorded under the same conditions. The curve of intensity of Lu 176 was then computed by the recorded curve of the hyperfine structure of Lu 176 (which was averaged over 5 orders of interference), and from the curve thus ascertained, the ratio (c/a) of the components of Lul76 was then computed. After considering the correction for the superimposition of the outlines of the components measured, the value 1.31 + 0.03 was obtained. These computations delivered the dependence of the values for o/a on the nuclear spin I as indicated in the above table. The ratio c/a measured with 1.31+0.03 is in good agreement with the nuclear spin I = 7, and also with the presuppositions which are based on the application of Hil'sen's scheme (Refs 2, 3). Also according to this scheme, the value I=7 is most probable. The next possible values I = 6 and I = 8 lie beyond the limits of error of the measurements described here. For

Card 2/3

Spectrescepic Determination of the Lu 176 Nuclear Spin

507/20-126-1-14/62

checking these measurements, only the spectral line Lu $4/\lambda$ 6463 a was used because of the small quantities of enriched preparation. Therefore, also measurements of other spectral lines of lutecium are required for a definite rejection of the spin values I \neq 7. The authors thank S. E. Frish and L. K. Peker for the discussion of the results, as well as V_0 S. Zolotarev for the supply of the enriched lutecium preparation. The authors also thank G. K. Yeremin for the supply of pure lutecium preparations of natural isotopic composition. There are 2 figures and 3 references, 1 of which is Soviet.

ASSOCIATION:

Leningradskiy gosudarstvennyy universitet im. A. A. Zhdanova (Leningrad State University imeni A. A. Zhdanov)

PRESENTED:

January 22, 1959 by A. A. Lebedev, Academician

SURMITTED:

January 13, 1959

Card 3/3

PALYSHEV, G.M.; SKIDAN, V.B.; FRADRIK, E.Ye.; CHAYDA, N.P.

Resolution of a monochromator with photoelectric recording. Opt.

i spektr. 7 no. 6:780-784 D *59. (MIRA 14:2)

(Monochromators)

SEMEMOV, R.I.; FADKIN, E.Ye.; CHAYKA, M.P.

Apparatus function of a Fabry-Perot spectrometer with a rectangular orifice plate. Opt. 1 spektr. 7 no. 6:785-788

[MINA 14:2]

(Spectrometer)

CHAYKA, M.P.; FRADRIN, E.Ye.

Method for transforming spectral line shapes and its application to the measurement of the temperature and other parameters of a light source. Opt. i spektr. 7 no. 6:820-823 D 159.

(MIRA 14:2)

(Spectrometer)

PHASE I BOOK EXPLOITATION

sov/5090

Zaydel', A. N., N. I. Kaliteyevskiy, L. V. Lipis, and M. P. Chayka

Emissionnyy spektral'nyy analiz atomnykh materialov (Emission Spectrum Analysis of Atomic Materials) Leningrad, Fizmatgiz, 1960. 686 p. 8,000 copies printed.

Ed. (Title page): A. N. Zaydel', Professor; Ed.: Ye. Ya. Shreyder; Tech. Ed.: A. A. Zabrodina.

PURPOSE: This book is intended for specialists in optics and spectral analysis.

COVERAGE: The book deals with the techniques of spectral analysis used in the determination of the purity of atomic materials. The work does not discuss determinations of components in alloys, including Nb-U and U-Al used in reactor construction, and in alkali metal alloys, nor does it describe the analysis of atomic raw materials (ores and primary products of their processing) since this type of materials can be treated by conventional

Card 1/15

Emission Spectrum Analysis (Cont.)

SOV/5090

spectral analysis methods. Ch. II, III, IX, XII, XIII, and XIV were written by A. N. Zaydel'; Ch. VI, X, and XI by N. I. Kaliteyevskiy; Ch. VII and VIII by L. V. Lipis; Ch. IV by M. P. Chayka; Ch. I by A. N. Zaydel' in cooperation with N. M. Kaliteyevskiy; and Ch. V. by M. P. Chayka and A. N. Zaydel'. The authors thank S. E. Frish, A. A. Petrov, S. M. Rayskiy, M. A. Yel'yashevich, A. A. Bashilov, V. V. Nalimov, and Ye. Ya. Shreyder. References accompany each of the three parts of the books.

TABLE OF CONTENTS:

Foreword

ť

9

Introduction


11

PART I. PRINCIPLES OF SPECTRAL ANALYSIS AND THE APPARATUS

Ch. 1. Principles of Emission Spectrum Analysis
1. Basic conditions

17

Card 2/15



SOV/51-8-1-3/40

Spectroscopic Determination of Nuclear Moments of Odd Gadolinium Isotopes

components. Gadolinium samples had compositions shown in Table 1:

Nr 1 had 97.3% Gd155, Nr 2 had 91.4% Gd157, Nr 3 (natural Gd) had

0.2% Gd152, 2.86% Gd154, 15.61% Gd155, 20.59% Gd156, 16.42% Gd157,

23.45% Gd158, 20.87% Gd160. Some of the results obtained are given

in Figs 2 and 3 and in Table 2. Fig 2 shows the relative positions

of the h.f.s. components of Gd157 and of Gd160, Gd158 and Gd156 in the

case of the 5015 Å line. Fig 3 shows the analysis of the Gd157

5015 Å (a) and 5103 Å (b) lines into their h.f.s. component. Table 2

lists the values of the hyperfine separation (f(in millikaysers) and

of calculated and quadrupole moments Q (in 10.24 cm2). Fig 4 shows the

transitions of the three lines investigated in schematic form. The

transitions of the three lines investigated in schematic form. The

authors found that gadolinium lines can be analysed into their components

only if four components are assumed for both Gd157 and Gd155. This

only if four components are assumed for both Gd157 and Gd155. This

with Low (Ref 5), Manenkov and Prokhorov (Ref 6). Depending on the

assumptions made, the authors obtained the following values for the

quadrupole moments: either

 $Q_{157} = 1.6$ and $Q_{155} = 1.2 \times 10^{-24} \text{cm}^2$,

or

Card 2/3

Spectroscopic Determination of Nuclear Moments of Odd Gadolinium Isotopes

 $Q_{157} = 2$ and $Q_{155} = 1.5 \times 10^{-24} \text{cm}^2$.

The magnetic moments were also found:

 $\mu_{157} = -0.40 \pm 0.04 \text{ n.m.}$ and $\mu_{155} = -0.32 \pm 0.04 \text{ n.m.}$

Consequently the moment ratios were:

 $Q_{155}/Q_{157} = 0.8 \pm 0.1$, $\mu_{155}/\mu_{157} = 0.79 \pm 0.02$.

The deformation parameters δ of the two nuclides were found to be $\delta_{157} = 0.37$ and $\delta_{155} = 0.31$, and their ratio was $\delta_{155}/\delta_{157} = 0.8$. The gyromagnetic ratios for the internal (g_E) and the collective (g_R) motion were also determined. They were $g_{K157} = -0.9$, $g_{K155} = -0.8$, $g_{K157} = g_{K155} = 0.7$; $g_{K155}/g_{K157} = 0.9 \pm 0.1$. Acknowledgments are made to V.S. Zolotarev for supplying separated gadolinium isotopes and to L.K. Peker for his advice. There are 4 figures, 2 tables and 21 references, 5 of which are Soviet, 10 English, 4 German, 1 Swiss and 1 Danish.

Card 3/3

SUBMITTED: June 19, 1959

s/056/60/039/004/008/048 B004/B070

24.6700

Kaliteyevskiy, N. I., Fradkin, E. Ye., Chayka, M. P.

AUTHORS:

Quadrupcle Moments of Odd Barium Isotopes

TITLE:

PERIODICAL:

Zhurnal eksperimental noy i teoreticheskoy fiziki, 1960,

Vol. 39, No. 4(10), pp. 954-956

TEXT: In order to determine the quadrupole moments of odd barium isotopes, a study of the deviation of the hyperfine structure from the isotopes, a study of the deviation of the hyperfine structure from the interval rule was made. The structure of $3P_1$ term of both the lines of the Ba I: $\lambda = 4599.7$ A and $\lambda = 4573.9$ A was determined by means of the hyperfine structure of highly enriched separated isotopes Ba 135 (89.3%) and Ba 137 (78.8%). Both the isotopes have spin 3/2. Therefore, the structure of the 3P₁ term is characterized by two independent intervals of the hyperfine structure whose magnitudes are related to the constants A and B of the interval function $W_F = W_J + (1/2)AC + B[C(C+1)]$ - (4/3)I(I+1)J(J+1); C = F(F+1) - I(I+1) - J(J+1); F = 5/2, 3/2, 1/2.

Card 1/2

Quadrupole Moments of Odd Barium Isotopes

S/056/60/039/004/008/048 B004/B070

The experimentally observed values of the intervals and the constants ${\tt A}$ and ${\tt B}$ are given in a Table. The quadrupole moments were calculated from the constants:

 $Q(Ba^{135}) = (0.25\pm0.12)\cdot10^{-24}$ cm², $Q(Ba^{137}) = (0.2\pm0.1)\cdot10^{-24}$ cm². Since for both the isotopes Q>0, Ba^{135} as well as Ba^{137} must have a hole in the $2d_3/2$ neutron level. The authors thank V. S. Zolotarev for making available the isotopes, L. K. Peker for discussions, and B. A. Strugach for calculations. There are 1 table and 9 references: 4 Soviet, 2 US,

ASSOCIATION: Leningradskiy gosudarstvennyy universitet (Leningrad State University)

SUBMITTED: May 12, 1960

Card 2/2

246200 1137, 1138, 1395

\$/054/61/000/001/003/008 B117/B203

AUTHORS:

Kaliteyevskiy, N. I., Chayka, M. P., Fradkin, E. Ye.

TITLE:

Application of methods of optical spectroscopy to study

the properties of atomic nuclei

PERIODICAL:

Vestnik Leningradskogo universiteta. Seriya fiziki i

khimii, no. 1, 1961, 25-33

TEXT: The authors studied the possibility of applying the methods of optical spectroscopy to study the properties of atomic nuclei. When checking these methods, they used, above all, the data found by themselves in 1959-60. The relative intensities of hyperfine structural components were measured with a photoelectric spectrometer with a Fabri-Pérot interferometer (Ref. 2: N. I. Kaliteyevskiy, G. M. Malyshev, M. P. Chayka. Optika i spektroskopiya, VI, 820, 1959). The light intensity of this instrument was higher by at least one order of magnitude than that of a monochromator with diffraction grating of equivalent resolving power. The investigation of only 1 mg of Lu203, which was

Card 1/5

Application of methods of ...

S/054/61/000/001/003/008 B117/B203

enriched with Lu 176 up to about 30 %, yielded quite clearly a spin value of I = 7. This investigation proved the importance of the optical method for determining the nuclear spin, as well as its suitability as compared with other methods. The same conclusions were drawn when considering results obtained in the measurement of sublevel ranges of hyperfine structure. With sufficient resolving power of the spectrometer, the reading of components with I>J gives a unique spin value. If the resolution of components is limited by the Doppler broadening it is generally possible to disintegrate, with sufficient uniqueness, the contour of the line into a certain number of components at a high signal-to-noise ratio. When determining mechanical nuclear moments, the interference method can, of course, not yet be regarded as perfect. The problem as to the accuracy of the method of determining magnetic and quadrupole moments requires a closer investigation, since direct measurement of these moments is impossible. In experimental determinations of hyperfine structural constants, systematic and random errors are unavoidable. Here, the authors deal with the role of random errors. An analysis of experimental data shows that in the investigation of a well resolved structure the measurement of hyperfine structural ranges is well possible at present

Card 2/5

Application of methods of ...

\$/054/61/000/001/003/008 B117/B203

with an accuracy of $\sim 0.5 \cdot 10^{-3}$ cm⁻¹. The errors of measurement increase with a worse resolution if it is necessary to disintegrate the contour. Table 3 gives the results of measurement of the hyperfine structure of barium isotopes as an example of such an estimate. All data are given in millikaiser (1 mks = 10^{-3} cm⁻¹). The errors of measurement are shown to be no less than 0.5 %. Approximation methods must be used to calculate absolute values of magnetic moments. For this reason, resonance methods permitting a direct measurement of μ are preferable to the optical method. In those cases where direct methods are not applicable, values of magnetic moments may be calculated both by optical and radiospectroscopic measurement with the same accuracy. When determining quadrupole moments, quantum-mechanical approximation methods are indispensable for all methods basing on the interaction of nucleus and electron shell. When estimating the accuracy of such calculations, the authors made the following statement: In single-electron systems, the entire theoretical calculation error is 5-10 % for magnetic moments, and 15-25 % for quadrupole moments. In each individual case, the admixture of many-electron states can be considered, and $(1/r^3)$ can be determined from the totality of data. This Card 3/5

\$/054/61/000/001/003/008 B117/B203

Application of methods of ...

increases the accuracy of determination. For many-electron systems, it is difficult at present to make a numerical estimate of calculation errors which may be different for each individual case. In each case where it is difficult to estimate the errors occurring in the calculation of nuclear moments from the hyperfine structure of the term investigated, it would be convenient to study other terms of the respective isotope. Similar values of moments for several terms of varying configuration give a certain security that errors do not become too high. It can be expected to increase the calculation accuracy by completer joint theoretical and experimental investigations of hyperfine and fine structures of atomic spectra, as well as of gyromagnetic atomic relations. The authors thank B. A. Strugach for making a number of computations. A. A. Manenkov, A. M. Prokhorov, and G. Kopferman are mentioned. There are 6 figures, 4 tables, and 18 references: 8 Soviet-bloc and 10 non-Soviet-bloc.

Card 4/5

S/054/61/000/001/003/008 B1.17/B203

Application of methods of ...

Legend to Table 3: Results of measurement of the hyperfine structure of odd barium isotopes. (a) Ranges and constants of hyperfine structure; (b) isotopes.

۸.		и Изотовы				
Интервалы и СТ	константы С	В	Ja 126		Barm	
5/2 + 5/2 + A B	3/2 1/2	137,	6±0,6 4±0,7, 0±0,2 2±0,6		93,1±0,4 151,5±0,7 37,7±0,2 -0,9±0,5	•

Card 5/5

S/051/61/010/001/003/017 E201/E491

11.4130

Zaydel', A.N., Razumovskiy, A.N. and Chayka, M.P.

AUTHORS:

A Spectroscopic Analysis of the Isotopic Composition

of Lithium

PERIODICAL: Optika i spektroskopiya, 1961, Vol.10, No.1, pp.15-18

TEXT: The authors describe a spectroscopic method for analysis of the isotopic composition of lithium, based on measurements of the component intensities of a resonance doublet at 6707.8 Å.

A hollow-cathode discharge tube was used as the light source. It is shown schematically in Fig.1. The isotopic structure was recorded using a Fabry-Perot interferometer. To separate out the required line, a diffraction-grating monochromator was employed. The optical part of the apparatus is shown in Fig.2, where 1 and 5 are slits, 2, 4, 6 and 9 are objectives, 3 is a diffraction grating, 7 is a Fabry-Perot interferometer enclosed in a chamber 8, 10 is an iris diaphragm, 11 is a receiver (a photomultiplier *** -22 (FEU-22)). The pressure in

the chamber 8 was varied periodically, using an automatic

Card 1/3

S/051/61/010/001/003/017 E201/E491

A Spectroscopic Analysis of the Isotopic Composition of Lithium

control device (Fig.3). The signal from the photomultiplier was passed to a d.c. amplifier and then to an automatic recorder 3111-09 (EPP-09). An example of the records obtained is given in Fig.4 for a sample containing 2% Li⁶. Neglecting selfabsorption and other effects, the concentrations were calculated from

$$\frac{c_{Li6}}{c_{Li7}} = \frac{I_b}{I_a} - \frac{1}{2}$$

K

where I_b, I_a are the intensities of the components of the 6707.8 Å line shown in Fig.5. A calibration curve used in calculations is given in Fig.6. The sensitivity of the method described here was 0.5% Li⁶. The errors were represented by a coefficient of variation of 0.15 to 0.7% for Li⁶ contents from 40 to 90%. The time required for each analysis was 10 to 15 min and the minimum amount of lithium was 5 to 10 µg (0.05 mg LiCl).

Card 2/3

S/051/61/010/001/003/017 E201/E491

A Spectroscopic Analysis of the Isotopic Composition of Lithium

Acknowledgments are made to T.N.Krylova for preparation of the interferometer plates and G.M.Malyshev for help in some stages of this work. The work was carried out in 1956-7. There are 6 figures and 10 references: 4 Soviet and 6 non-Soviet (one of which is translated into Russian).

C

SUBMITTED:

January 21, 1960 (to the Editor of "Atomnaya Energiya") April 16, 1960 (to the Editor of "Optika i

Spektroskopiya")

Card 3/3

TURKIN, Yu.I.; CHAYKA, M.P.

Anomalous ratio of the intensities of the hyperfine structure components of indium lines. Opt, i spektr. 11 no.5:695.
N '61.

(Indium-Spectra)

S/048/61/025/001/020/031 B029/B060

24.6700

AUTHORS: Kaliteyevskiy, N. I., Chayka, M. P., Pacheva, I. Kh.,

Fradkin, E. Ye.

TITLE: Nuclear moments of odd isotopes of gadolinium

PERIODICAL: Izvestiya Akademii nauk SSSR. Seriya fizicheskaya, v. 25,

no. 1, 1961, 111-114

TEXT: This is a report of studies which have been described in a previous preliminary communication. Several data have now been better defined by additional measurements and by improving the calculation method. The authors used a photoelectric spectrometer and a Fabry - Perot spectrometer to study the hyperfine structure of the three lines of GdI:

 $\lambda = 5015 \text{ A } (z^{11}G_9 - a^{71}F_8); \lambda = 5103 \text{ A } (z^{11}G_8 - a^{11}F_7) \text{ and}$

 $\lambda = 4743 \text{ A } (y^{11}F_3 - a^{11}F_4)$. The measurements were made on separated isotopes of gadolinium with a high-purity degree (Gd¹⁵⁵ - 97.3%,

Card 1/6

89254

Nuclear moments of odd isotopes of ...

S/048/61/025/001/020/031 B029/B060

Gd¹⁵⁷ - 91.4%). The components of the fine structure of gadolinium lines are so close to one another (15 to 20 mK) that the fine structure under the given experimental conditions could not be resolved. It can be resolved only if one presupposes four sublevels of the hyperfine structure of the investigated energy levels of Gd¹⁵⁷ and Gd¹⁵⁵. This unequivocally yields for both isotopes the spin 3/2. The position of the components of the hyperfine structure was determined on the basis of the splitting of the line structure taking account of all superimposing isotopes belonging to other elements. The calculations were carried out for the four intensive diagonal components of the line investigated. The three independent intervals $\sigma(1-2)$, $\sigma(1-3)$, $\sigma(1-4)$ were experimentally determined for every line of the two isotopes. The ratio of the magnetic moments of Gd¹⁵⁵ and Gd¹⁵⁷ was established by the direct combination of the experimental data:



 $\frac{\mu_{155}}{\mu_{157}} = \frac{\sigma_{155}(1-2) - \sigma_{155}(1-3) + \sigma_{155}(1-4)}{\sigma_{157}(1-2) - \sigma_{157}(1-3) + \sigma_{157}(1-4)}.$ The ratio of the quadrupole

moments of Gd¹⁵⁵ and Gd¹⁵⁷ can be calculated with a good accuracy by

Card 2/6

0, _,_

Nuclear moments of odd isotopes of ...

S/048/61/025/001/020/031 B029/B060

Casimir's formula. The results of calculations carried out by two different methods are given in Table 1. The value of the ratio of magnetic moments thus found is in good agreement with more recent and more accurate measurements of this quantity by the method of the paramagnetic resonance. The value $Q_{155}/Q_{157}=0.8\pm0.1$ found by the authors contradicts, however, the spectroscopic measurements by O. R. Speck, who found Q_{155} Q_{157} . Therefore, it is of interest to compare the data found by the authors with results obtained by other methods. The most accurate method is evidently that by V. Ramsak et al. (Ref. 10). Like the authors of the present article, those authors also found $Q_{155} < Q_{157}$ but a difference appears in the qualitative evaluation of Q_{155}/Q_{157} . For the calculation of the absolute values of the magnetic moment and the quadrupole moment from spectrometric measurements it is necessary to estimate the matrix elements $\langle H(0) \rangle$ and , which is, however, possible only by approximation. Card 3/6

X

89254

Nuclear moments of odd isotopes of ...


5/048/61/025/001/020/031 B029/B060

authors found $Q_{155} = 1.45 \cdot 10^{-24} \text{ cm}^2$ and $Q_{157} = 1.8 \cdot 10^{-24} \text{ cm}^2$. The deformation parameters were then estimated from the values of the intrinsic quadrupole moments: $\delta_{155} = 0.27$ and $\delta_{157} = 0.33$. Finally, for the gyromagnetic ratio the authors found $g_{K} 155/g_{K} 157 = 0.9$, which is in good agreement with experimental data published by other authors. V. S. Zolotarev is thanked for having supplied the pure isotopes and L. K. Peker for his discussions. The article under consideration is the reproduction of a lecture delivered at the 10th All-Union Conference on Nuclear Spectroscopy, which took place in Moscow from January 19 to 27, 1960. There are 1 figure, 2 tables, and 12 references: 5 Soviet-bloc and 6 non-Soviet-bloc.

ASSOCIATION: Nauchno-issledovatel skiy fizicheskiy institut Leningradskogo gos. universiteta im. A. A. Zhdanova (Scientific Research Institute of Physics of Leningrad State University imeni A. A. Zhdanov)

Card 4/6

Legend to Table 1: Ratios of magnetic and quadrupole moments of odd gadolinium isotopes								
ra	io	$\lambda = 5015 A$	λ = 5103 A	λ =. 4743 A	mean value			
¹ 155 ¹ 157		0.80±0.02	0.77±0.01	0.79±0.02	0.78±0.03	15		
^ໄ 155 1ຍ		0.76±0.04 0.76±0.03	0.82±0.02 0.82±0.05	0.88±0.05 0.86±0.07	0.8 ±0.1 0.8 ±0.1			
						20.		
						以		



5/051/62/012/003/002/016 E032/E314

Razumovskiy, A.N. and Chayka, M.P.

Measurement of the isotopic shifts on the AUTHORS:

resonance line of barium TITLE:

Optika i spektroskopiya, v. 12, no. 3, 1962, PERIODICAL:

TEXT: The authors report measurements of the isotopic shift of λ 5535.6 Å BaI (6s s o - 6sp P₁), using highly-enriched

separated isotopes. Instead of the usual photographic method, the hyperfine structure was recorded photo-electrically. The main object of the present paper is to describe the experimental methods employed to reduce random and systematic errors. The photo-electric recording of the barium line was carried out with the aid of the method described in an earlier paper (Ref. 5 -Kaliteyevskiy, N.I., Malyshev, G.M. and Chayka, M.P. - Opt. i spektr., 6, 820, 1959). A Fabry-Perot etalon with a separation of 7 cm and reflection coefficient of the order of 93% was employed. An invar separator was used to reduce the temperature

Card 1/2

S/051/62/012/003/002/016 E032/E314

Measurement of the

effect. An analysis is given of the effect of temperature and pressure changes on the position of the recorded maxima. Devices are described whereby these changes may be compensated in practice. The measured isotopic shifts are as follows: $O(Ba^{158})$, $+5.7(Ba^{137})$, $+4.2(Ba^{136})$, $+7.6(Ba^{135})$ and $+4.7(Ba^{134})$. The corresponding results reported by J.E. Mack (Phys.Rev., 109, 820, 1958.— Ref. 4) are said to have been O(0, +4.7, +3, +6.7) and O(0, +4.7, +3,

SUBMITTED: : March 11, 1961

Card 2/2

36501

S/051/62/012/003/012/016 E202/E435

AUTHORS:

Kagan, Yu.M., Perel', V.I., Chayka, M.P.

TITLE:

Theory of optical signal amplification using a medium with negative absorption

PERIODICAL: Optika i spektroskopiya, v.12, no.3, 1962, 427-433

TEXT: Problems of amplifying an optical signal by means of negative absorption medium are discussed but without references to the generation. Formulae for the integral amplification of the incident signal A, are derived for the Lorentz and Doppler profiles, the integrals being evaluated by means of Bessel's function and power series respectively. In the case of high amplification, i.e. $k_0 l \gg 1$, these are

 $A_{Lor} = \frac{e^{k_0 l}}{\sqrt{\pi k_0 l}}$; $A_{Dopp} = \frac{e^{k_0 l}}{\sqrt{k_0 l}}$

where k_0 is the amplification coefficient at the centre of the line and ℓ is the thickness of the medium. These considerations are applied to a parallel mirror containing the active medium Card 1/2

Theory of optical signal ...

S/051/62/012/003/012/016 E202/E435

within and a uniform medium outside the mirrors. Relations are developed for the ratio of incident \mathcal{J}_0 , and emergent \mathcal{J}_0 , intensities of the beam, which in the case of ideal mirror and narrow beam are

$$\frac{\vec{d}}{\vec{d}_0} = \frac{(1-r)^2 e^{kb}}{1-r^2 e^{2kb}}$$

The ideal case is developed further to account for real finite mirrors with surface defects. The effects of the edges on the width of the diffraction rings and the departures from optical flatness are considered and a working example based on experimentation of A.Javan and associates (Ref. 6: Phys. Rev., Letters, 6, 1961, 106) are given. The work is completed by considering frequency distribution in the amplified beam in the absence of interference for the Doppler and Lorentz profiles. There are 3 figures.

SUBMITTED: July 24, 1961

Card 2/2

49.3500 9,2576 38531

s/051/62/012/006/019/020 E036/E418

AUTHORS:

Card/1/2

Fradkin, E.Ye., Chayka, M.P.

TITLE:

Continuous radiation of a three level quantum

generator with an optical pump

PERIODICAL: Optika i spektroskopiya, v.12, no.6, 1962, 796-798 T.H.Maiman (Phys. Rev., v.123, 1961, 1145) has solved the steady state equations for a three level quantum generator by using a linear approximation. In the present paper exact solutions are presented, thus taking into account the dependence of the populations N_2 and N_1 of the levels 1 and 2 (Fig.1) on the probability of induced transitions. Expressions are obtained for the difference in population $(N_2 - N_1)$ of the two levels and for the radiation power as a function of the pump radiation flux density F. Curves are plotted using data from T.H.Maiman's papers (Phys.Rev., Letters, v.4, 1960, 564; It is shown Phys. Rev., v.123, 1961, 1151) on the ruby laser. that with increasing pump power the radiation power goes to a limiting value. Also as $F \rightarrow \infty$, $(N_2 - N_1)/N_0$ goes to the where N_0 is the total number of atoms and Q_M^0/Q_C limit QM/QC

Continuous radiation ...

S/051/62/012/006/019/020 E036/E418

are the "Q's" of the material with all the atoms in the ground state and of the cavity respectively. This is stated to be equivalent to the usual condition for generation in the linear approximation. It is concluded that saturation through (N_2-N_1) is achieved at small pump powers significantly sooner than saturation by generated power and the limiting condition for (N_2-N_1) is fulfilled over the whole range of generation. There are 2 figures.

SUBMITTED: January 17, 1962

Fig.1. The three level diagram.

W12, W13, W21, W31 - induced transition probabilities.

S₃₂ - transition probability for non-radiative transitions.

A₂₁, A₃₁ - transition probabilities for spontaneous transitions.

Card 2/2

MARKOVA, G. V.; KALITEYEVSKIY, N. I.; CHAYKA, M. P.

"Observation du Croisement des Sous-Niveaux Zeeman dans le Natrium."
report submitted to 11th Intl Spectroscopy Colloq, Belgrade, 30 Sep-4 Oct 63.
Physics Inst, Leningrad Univ.

CHAYKA, M.P.

Measuring the reflection coefficients of light-dividing layers.

Opt. i spektr. 14 no.1:159-161 Ja '63. (MIRA 16:5)

(Reflection (Optics))

CHAYKA, M.P.; YAKOBSON, N.N.

Filter for optical pumping on cesium. Opt. i spektr. 16 no.5; 899-901 My (64. (MIRA 17:9)

ACCESSION NR: AP4035482

8/0051/64/016/005/0899/0901

AUTHOR: Chayka, M.P.; Yakobson, N.N.

TITLE: Filter for optical pumping of cesium vapor

SCURCE: Optika i spektroskopiya, v.16, no.5, 1964, 899-901

TOPIC TAGS: gas laser, laser pumping method, optical filter, cesium

ABSTRACT: For effective optical pumping to one of the hyperfine sublevels of the ground state of alkali metal vapors one must use light in which the intensity of the hyperfine components does correspond to the intensity rule. In the present paper there is proposed an appropriate selective filter based on a Fabry-Perot interferometer. This is diagramed in the figure (Enclosure 01). The present filter was designed specifically for pumping to one of the hyperfine sublevels of the ground state of cesium, but the parameters can obviously be modified for other pumping purposes. The Fabry-Perot interferometer consists of a fused quartz plate with a multilayer, dielectric reflecting coating on both sides (reflection coefficient about 67%). "The coatings were applied in the laboratory of T.N.Krilova." The lens 2 focuses the light on the ring diaphragm. This consists of a series of alternating

Cord 1/3

ACCESSION NR: AP4035482

transparent and opaque rings (the glass plate is first coated with silver and then with black varnish and the double coating is removed with a brass cutter to form the transparent rings). The number of rings that can be used is limited: at a distance of 10 orders from the center the line shifts by half an order relative to the next and the selectivity is impaired. The filter assembly must be maintained at constant temperature. Alignment of the diaphragm, however, is easy. Estimates of the efficiency of the given filter indicate that about % of the useful light is stopped by the filter and about 9% of the unwanted light is transmitted. The various advantages of the filter are discussed. Originatichas: 5 formulas and 1 figure.

ASSOCIATION: none

SUBMITTED: 05Jun63


SUB CODE: OP, EC

DATE ACQ: 22May64

ENCL: 01

OTHER: 009

Cend 2/3



L 2136-65 EWT(1) SSD/ASD(a)-5/ASD(b)/ASD(m)-3/AFWL/AFETR/AS(mp)-2/ ESD(c)/ESD(gs)/ESD(t)/RAEM(t) ACCESSION NR: AP4044840 S/0051/64/017/003/0319/0326

AUTHORS: Markova, G. V.; Chayka, M. P.

TITLE: Observation of the crossing of magnetic sublevels of the excited states of cesium and sodium

SOURCE: Optika i spektroskopiya, v. 17, no. 3, 1964, 319-326

TOPIC TAGS: cesium, sodium, polarization, resonant emission, interference effect, level crossing, Zeeman effect

ABSTRACT: The polarization of resonant emission of the sodium line 5,890 Å (3 $^{2}P_{3/2}$ ---2 $^{2}S_{1/2}$) and the cesium line 4,555 Å (7 $^{2}P_{3/2}$ --6 $^{2}S_{1/2}$) was investigated in fields from zero to 40 Oe. The experimental set-up was built around a cell containing the vapor of the alkali metal, placed in a constant magnetic field, and exposed to polarized light from a lamp excited by a high-frequency generator

Card 1/3

ACCESSION NR: AP4044840

and containing the same vapor. The observation was carried out along the field, so as to make the observed polarization to be caused only by interference phenomena. In addition to the maximum at H = 0 (the Hanle effect) additional polarization maxima were observed, due to the crossing of the Zeeman sublevels in the external magnetic field. The experimental values of the polarization (19.6 and 16% for sodium and cesium, respectively) agree well with the theoretical values (19.8 and 15.6%). Results yielded for the lifetime of the 3 2p 3/2 of

sodium a value of 1.63 \pm 0.05) \times 10⁻⁸ sec, which agrees well with other measurements. "The authors thank S. E. Frish and N. I. Kaliteyevskiy for a discussion of the present article." Orig. art. has: 5 figures and 3 formulas.

ASSOCIATION: None


SUBMITTED: 14Jan64

ENCL: 01

SUB CODE: OP

NR REF SOV: 006 OTHER: 011

"APPROVED FOR RELEASE: 06/12/2000 CIA-RDP86-00513R000308210014-2



Lanisi-65 ENG(1)/ENA(N)/PBD/ENT(1)/ENT(M)/EPF(c)/EEC(k)-2/EEC(t)/T/ENP(t)/
EEC(b)-2/ENP(k)/ENP(b)/ENA(M)-2/ENA(M) Pn-h/Po-h/Pf-h/Pr-h/Peb/Pi-h/Pl-h

SSD(c)/SSD/AFWL/ASI(M)-2/ENA(M)/ESD(cm)/ESD(t)/IJP(c) NG/JD

ACCESSION NR: APHO41833

AUTHOR: Kaliteyevskiy, N. I: Razumovskiy, A. N.; Chayka, M. P.; Cherenkovskiy,

V. A.

TITIE: Experiments with gaseous Lasers 25

SOURCE: Leningrad. Universitet. Vestnik. Seriya fiziki i khimii, no. 10, 1964,

40-46

TOPIC TAGS: gaseous laser, continuous gaseous laser, laser beam structure, helium neon laser, stimulated emission.

ABSTRACT: The authors have experimental with a continuous gas lase. (Ne:He=1:7) working on a wavelength of 1.15 \(\mu\) which corresponds to the 2.3-2p transition in neon. The study consisted of an investigation of;1) the intensity of the generated power (stimulated radiation) as a function of the input power, the diameter of the discharge tube, and of gas pressure; 2) the contribution to radiation of the various parts of the lischarge; and 3) the structure of the generated beam. It was confirmed in the authors experiments that the intensity of the generated beam reaches a maximum with increase of the input power, and then decreases. In addition to the 1.15 \(\mu\) line, the 1.16 \(\mu\) line (much weaker than 1.15) was also

Card 1/2

0

L 20181-65

ACCESSION NR: AP4041833

observed with a diffraction grating. It disappears at very high input. The photograph of the beam shows a ring regardless of the adjustment of the lens. This is explained by the coherence of the stimulated radiation. Orig. art. has: 8 figures.

ASSOCIATION: None

SUBMITTED: 17Jan64 ENCL: 00

SUB CODE: EC NO REF SOV: 003 OTHER: 001

Card 2/2

L 64006-65 ENA(k)/FBD/ENT(1)/EEC(k)-2/T/EEC(b)-2/ENP(k)/ENA(m)-2/ENA(h) SCTB/IJP(c)

ACCESSION NR: AP5019760

UR/0051/65/019/002/0255/0263
621.375.9:53

AUTHOR: Zeyger, S. G.; Kaliteyevskiy, N. I.; Fradkin, E. Ye!; Chayks, M. F.

TITLE: The structure of the radiation field of a gas laser with spherical mirrors

25/14

SOURCE: Optika i spektroskopiya, v. 19, no. 2, 1965, 255-263

TOPIC TAGS: laser output, gas laser, spherical mirror laser

ABSTRACT: The intensity distribution of a gas laser with spherical mirrors with a high coefficient of reflection was studied experimentally and theoretically. The dependence of the size of the laser beam on the distance from the resonator center and/or the focusing lens was plotted. The amount of emitted energy which can be focused into a given angle by means of two simple lenses was found to be higher than can be achieved with equal distribution of the intensity of the front of the beam. Orig. art. has: 6 figures and 21 formulas. [YK]

ASSOCIATION: none

SUBMITTED: 19Sep64 ENCL: 00 SUB CODE: EC NO REF SOV: Q02 OTHER: 002 ATD PRESS: 4057

Cord 1/1 (100)

L 5426-66 EWT(m)/EWP(t)/EWP(b) AP5019771 AUTHOR: Kallas, Kh.; Markova, G.; Khvostenko, G.; Chayka, M. IJP(c) TITIE: Determination of the hyperfine structure constants of cesium from the crossing of magnetic sublevels UR/0051/65/019/002/0303/0306 SOURCE: Optika i spektroskopiya, v. 19, no. 2, 1965, 303-306 TOPIC TAGS: cesium tion, Zeeman effect hyperfine structure, spectral line, spectral energy distribu-ABSTRACT: This is a continuation of earlier work (Opt. 1 spektr. v. 17, 319, 1964) and is devoted to a more precise measurement of the magnetic fields for the crossing ABSTRACT: This is a continuation of earlier work (Opt. 1 spektr. v. 17, 319, 1964) of the Zeeman sublevels of the 7 sp./s state in cesium. and to similar measurements of the Zeeman sublevels of the 7 ap. 1/2 state in cesium, and to similar measurements with constant C = 17.77 ± 0.01 Oe/amp, the coil axes being directed along the horifor the 6 2P3/2 level. The magnetic field was produced by a pair of Helmholz coils component of the earth's magnetic field. The vertical component was offset with constant C = 17.77 ± 0.01 Oe/amp, the coil axes being directed along the horizontal component of the earth's magnetic field. The vertical component was offset rocked for 7 3p₁/2 and Sontal component of the earth's magnetic field. The vertical component was offset for 6 2p. /o. Expansion coefficients for the three level-crossing fields are calcuby supplementary coils. Three level crossings each were observed for 7 3p1/2 and 52p3/2. Expansion coefficients for the three level-crossing fields are calcu-6 2P3/2. Orig. art. has: 9 formulas and 1 table. C_{ord} 1/2

L 5426-66	and the second s	and the second s		0	
ACCESSION NR: AP5019771					
ASSOCIATION: none SUBMITTED: 12Feb65	ENCL: 00	SUB CODE:	ı OP		
NR REF SOV: 002	OTHER: COL				

11935-66 EWT(m)/EWP(t)/EWP(b) IJP(c) JD/JG ACC NR: AP6001653 SOURCE CODE: UR/0051/65/019/006/0968/0972

AUTHOR: Al'tman, B.L.; Chayka,

ORG: None

TITLE: Determining the lifetime of the excited state of double resonance experiments cesium 7

SOURCE: Optika i spektroskopiya, v. 19, no. 6, 1965, 968-972

TOPIC TAGS: cesium, magnetic resonance, magnetic field, excited state

ABSTRACT: The superfine structure of the 72p3/2 level of cesium is briefly described and it is shown that in weak magnetic fields each of the four component sublevels is fragmented into Zeeman sublevels with its own Lande factor $g_{\rm F}$. An explanation is given of the double resonance method proposed by A. Kastler and J. Brossel (C.R. Acad. Sci., 229, 1213, 1949). The double resonance signal is proportional, first of all, to the difference of populations. Most favorable was found to be a population by light having a polarization parallel to the magnetic field. The advantages of radiation by light with π -polarization are discussed, and the dependence of the double resonance signal amplitude on the magnetic field is analyzed. It is shown that resonances belonging to different superfine levels lie very close to each other, so that their experimental resolution is an almost hopeless task. Since the signal from the $F \approx 5$

1/2 Card

UDC: 539.143.43:535.53:546.36

L 11935-66 ACC NR. AP6001653

力

level is far greater than the others, the authors assumed that the experimentally observed signal is caused only by transitions between magnetic sublevels of the superfine state with F = 5. The experimental setup employed for the observation of the double resonance signal is described. A resonance cell with cesium vapors was located in a constant magnetic field and illuminated by polarized light from a lamp containing the same vapors. The lifetime of the excited state of the cesium $7^2P_3/2$ was measured by the width of the magnetic resonance lines: = $(2.5 \pm 0.6) \cdot 10^{-7}$ sec. The Lande factor, estimated according to the resonance transition frequency, was gr = 0.45 0.05. It was also found that the position of resonance is determined by the particular magnetic field in which the distance between the Zeeman sub-levels is equal to the HF field frequency. The width of the magnetic resonance lines between the excited states, moreover, is a function primarily of the width of the levels. A formula expressing this function is presented. The magnetic resonance lines were found to expand under the effect of the HF field and nonuniformities in the permanent magnetic field. A table is given for a comparative study of lifetime calculations made by different authors using different methods. Authors thank A. N. Razumovskiy for adjusting the magnet, R. I. Semenov for assisting in the work, and N. I. Kaliteyevskiy for discussing the results. Orig. art. has: I table and 5 figures.

20 / SUBM DATE: 20Jul64 / ORIG REF: 005 / OTH REF: 009 SUB CODE:

APPROVED FOR RELEASE: 06/12/2000

CIA-RDP86-00513R000308210014-2"

Card 1/2

L L1096-66 EWT(1)/EEC(k)-2/FBD/EWP(k)/T LIP(c) WO SOURCE CODE: UR/0051/66/021/002/0258/0260 ACC NRi AP6026983 AUTHOR: Kaliteyevskiy, N. I.; Popov, M. M.; Rymarchuk, Yu. A.; Tolchinskaya, T. B.; Chayka, M. P. ORG: none TITLE: Gas laser generation power in nearly confocal resonators SOURCE: Optika i spektroskopiya, v. 21, no. 2; 1966, 258-260 TOPIC TAGS: gas laser, neon helium laser, infrared laser, LASER ENERGY, DEON, HELIUM ABSTRACT: A qualitative explanation of the mechanism responsible for the appearance of the maximum of power generation in a nearly confocal resonator of a gas laser is offered. The generation of a neon-helium laser at λ = 0.63 and 1.15 μ was studied. It is shown that because of a decrease in the figure of merit in the region of instability of the generation, a minimum should appear on the curve representing the generation power as a function of L (L being the distance between the mirrors). The width of the minimum is equal to the width of the instability region traversed, and is determined by the difference in the mirror radii aR. In a study of a resonator with mirrors whose radii $R_1 = R_2 = 250$ cm within 0.4 cm, minima were obtained whose width was greater than 0.4 cm and was varied by shifting the discharge tube along the resonator axis and replacing the tube by another. These experimental data were attributed to the distorting influence of the exit windows of the discharge tube. It is shown UDC: 621.375.9:535 (206.3)

that a tube window built with an error of $\sim \frac{\lambda}{2}$ and consisting of a lens with a focal length of 100 m causes the appearance of a region of instability of width $\Delta L = 6$ cm at R = 250 cm. The region of instability was found in similar fashion for a resonator where the space between one of the mirrors and the window is filled with a gas with refractive index N. different from the refractive index of air, N_a. In this case, $L = \frac{N_c - N_a}{N_c}$ R. These calculations were confirmed in a series of experiments. Authors are grateful to E. Ye, Fradkin for his discussion and to A. N. Razumovskiy for his assistance in the experiment. Orig. art. has: 2 figures and 1 formula. [27] SUB CODE: 20/ SUBM DATE: 14Mar66/ ORIG REF: 005/ OTH REF: 002/ ATD PRESS: 5057

APPROVED FOR RELEASE: 06/12/2000 CIA-RDP86-00513R000308210014-2"

Card 2/2

VECHER, A.S.; CHAYKA, M.T.


Photosynthetic activity of the green potato tubers. Dokl. AN BSSR 6 no.5:331-333 My '62. (MIRA 15:6)

1. Institut biologii AN BSSR.
(Photosynthesis)
(Potatoes)

VECHER, A.S. [Vechar, A.S.]; MAS'KO, A.A.; CHAYKA, M.T.

Change in the plastids of potato tubers under the influence of many days of light. Vestsi AN RSSR Ser. biial. nav. no.3:74-80

•64 (MIRA 18:1)



BOBOREKO, E.A.; KALYUZHNYY, M.Ya.; CHAYKA, N.D.; ABRAMOVICH, M.M.; SHILOV, Yu.P.; DRUZHININA, A.T.; ZYBIN, S.Ye. [deceased]; BATIKOV, L.S.

Improving the process of yeast growing on wood hydrolyzates. Gidroliz. i lesokhim.prom. 17 no.8:22-25 64.

(MIRA 18:1)

1. Gosudarstvennyy nauchno-issledovatel*skiy institut gidroliznoy i sul*fitno-spirtovoy promyshlennosti, Leningrad (for Boboreko, Kalyuznyy, Chayka, Abramovich). 2. Ivdel*skiy gidroliznyy zavod (for Shilov, Druzhinina, Zybin, Batikov).

GHARA, F.I.

First factory school in the sugar industry. Sakh. brom. 37 no.2:
(MIRA 16:5)
75(155) F '63.
(Vocational education) (Sugar industry)

CHAYKA, N. K.

Jun 48

PA 43/49T42

USSR/Engineering Construction Industry Bibliography

"Soviet Technical Periodicals" 2 P

"Stroi Prom" No 6

Reviews technical periodicals, among other: N. K. Chayka's "Production of Tower Cranes for Residential Constructions," I. M. Iog's "Mechanization of Limestone Unloading," D. S. Ioffe's "Mobile-Suspension Cableway," etc.

43/49142

DORONENKO, F.G.; CHAYKO, N.P.

Effect of the rate of mining on the duration of strip mine construction. Trudy Inst.gor.dela AN Kazakh.SSR 14:98-107 (MIRA 18:1)

In the Coordinating Council on Welding. Avtom.svar. 15 no.4:94-95
Ap !62.

(Welding-Congresses)

ACC NR: AP6030984 (N) SOURCE CODE: UR/0378/66/000/004/0025/0032

AUTHOR: Matsevityy, L. V.; Chayka, N. S.

ORG: none

TITLE: Coding the states of a sequential device on taking into account certain logic properties of the incorporated elements

SOURCE: Kibernetika, no. 4, 1966, 25-32

TOPIC TAGS: logic design, communication coding, computer coding, coding evaluation

ABSTRACT: The article deals with a method of coding which makes it possible, for a given number of coincidence-element inputs, to find the codes of internal states in such a way as to dispense with the need to construct multistage coincidence. This pertains to a sequential device for which each possible set of values of signals at its input terminals is denoted by a symbol of the alphabet X and each possible set of values of signals at the output terminals is denoted by a symbol of the alphabet Y. Since any device may be considered to consist of two parts of which one represents memory elements and the other the combinational scheme, any possible set of signal values at the input channel of any memory element will be denoted by a

Card 1/2

UDC: 681.142.1.01

APPROVED FOR RELEASE: 06/12/2000 CIA-RDP86-00513R000308210014-2"

<u>nere en la caractera de la ca</u>

ACC NR: AP6030984

symbol of the alphabet U and any possible set of signal values at the output channel of any memory element will be denoted by a symbol of the alphabet V. At such a notation each pair of symbols of the alphabets X and V corresponds to a pair of symbols of the alphabets U and Y. A particular case of binary memory elements is considered for which a symbol of the alphabet V at any time instant is uniquely determined by the set of states of these elements, a set which, on ordering, will be termed a code. Each symbol of the alphabet V uniquely corresponds to a code and in the general case for m memory elements the establishment of this correspondence requires examining the entire code of length m. Coincidence-realizing logic elements have a limited number g of input channels, which often is smaller than m + p (where p is the number of channels used to code a symbol of the alphabet X). Therefore, it is of interest to develop such a coding of states as would result in assigning to each state a specific code segment with a length of not more than n < m, which differs from the same code segment of any other state, and where n is chosen so that the sum of n + p would not exceed g. It is shown that this can be accomplished by subdividing the set of N states into disjoint subsets of 2n-1 states each. Suppose $N = s(2^{n}-1) + q$, where $q < (2^{n}-1)$. Thus, we have s subsets of $2^{n}-1$ states each and one subset of q states. We code the states of one of the subsets by means of the sets of values of n variables and the single remaining set will correspond to all the sets not entering in the select= ed subset. The sets of values of n variables represent the first segment of the code of all states. This operation is repeated until the code segment of each state are determined, and a pertinent coding algorithm is described. SUB CODE: 09, 12, 06/ SUBM DATE: 17Jul65/ ORIG REF: 004/ OTH REF: 004

Card 2/2

FRUMIN, I.I.; CHAYKA, O.V.

In the Coordinating Council on Welding. Avtom. svar. 15 no.8:93-95 Ag '62. (MIRA 15:7)

CHAYKA, P.A.

Use of the universal "TISS" radiometer for the fluorometric determination of coproporphyrin. Lab. delo no. 12:719-723 '64. (MIRA 18:1)

1. Kafedra obshchey gigiyeny (Zaveduyushchiy - doktor med.nauk prof. P.I.Barannik) Kiyevskogo meditsinskogo instituta.

CHAYKA, T.P.

Chemical composition of commercial natural honey. Vop. pit. 20 no.6:75-76 N-D *61. (MIRA 15:6)

1. Iz Yaltinskoy gorodskoy sanitarne epidemiologicheskoy stantsii. (HONEY)

CHAYKA, T.P.


Vitamin C activity in commercial vegetable products. Vop.pit. 22 no.1291-92 Ja-F*63 (MIRA 16:11)

1. Iz sanitarno-epidemiologicheskoy stantsii, Yalta.

*

CHAYKA, T. and ANICHKOV, N. N.

Weber die Verteilung und die Ablagerungsorte der Tusche nach subkutanen und intraperitonealen Einfuhrung. Zeitschr. für die gesamte experimentelle Medizin. 92, 3/4, 497-516, 1933.



CHAYKA, T.V., dotsent.

Changes in the oral mucosa in dysentery. Stomatologiia no.5:8-11 (MLRA 7:1)

1. Is kafedry patologicheskoy anatomii (saveduyushchiy - professor L.V.Sipovskiy) Leningradskogo meditsinskoge stomatologicheskogo instituta (direktor - professor R.I.Gavrilov).

(Nouth) (Dysentery) (Mucous membrane)

CHAYKA, T. V., Doc Med Sci -- (diss) "Experimental and pathologico-anatomic studies on the morphology of alimentary exhaustion." Len, 1957. 24 pp (1st Len Med Inst im Academician I. P. Pavlov), 200 copies (KL, 2-58, 115)

-59-

SHAMOV, V.N.; BABCHIN, I.S.; BADMAYEV, K.N.; CHAYKA, T.V.; MANDEL BOYM, A.B.; NEYMAN, B.G. (Loningred)

Some observations on radiogold therapy in inoperable cerebral tumors. Vop.neirokhir. 23 no.3:1-6 My-Je 159. (MIRA 12:8)

1. Manchno-issledovatel skiy neyrokhirurgicheskiy institut imeni prof.A.L.Polenova.

(BRAIN MEOPLASMS, ther.
radiogold in inoperable tumors (Rus))
(GOLD, radioactive,

ther. of cancer of brain, inoperable cases (Hus))

MYUL'BERG, A.A.; SYTINSKIY, I.A.; CHAYKA, T.V.

Electrophoretic separation of soluble proteins in tumors of the human brain. Vop.med.khim. 8 no.1:58-64 Ja-F 162. (MIRA 15:11)

1. Laboratoriya khimii belka Leningradskogo gosudarstvennogo universiteta imeni A.A.Zhdanova, i patologoanatomicheskaya laboratoriya Instituta neyrokhirurgii imeni A.L.Polenova, Leningrad.
(BRAIN_TUMORS)

(PROTEINS)

(ELECTROPHORESIS)

FEVENER, L.Z.; TOMINE, Ye.D.; CHAYKA, T.V.

Cytospectrophotometric research on the DNA content of human brain tumor cells, Vop. med. khim. 10 no.4:379-386 J1-Ag 164. (MIRA 18:4)

1. Laboratoriya khimii belka Fiziologicheskogo instituta imeni A.A.Ukhtomskogo Leningrad I laboratoriya patologicheskoy anatomii Nauchno-issledovatel'akogo neyrokhirurgichbskogo instituta Leeni Polenova, Leningrad.

СНАУК	A, V.	
	Adjustment of interchangeable lenses. [61. (Cameras)	Sov.foto 21 no.12:28-29 D (MIRA 14:12)

ACCESSION NR: AP4039602

5/0126/64/017/005/0737/0743

AUTHORS: Aksenov, G. I.; Morozov, N. P.; Chayka, V. A.

TITLE: Investigations of the terminal structural deformations and residual austenite quantity in quenched rolled stoel

SOURCE: Fizika metallov i metallovedeniye, v. 17, no. 5, 1964, 737-743

TOPIC TAGS: rolled steel, martensite, structural deformation, residual austenite, annealing, quenching medium, steel 9Kh

ABSTRACT: The effect of heating and cooling (in the martensite temperature range) on the magnitude of relative structural deformation and on the quantity of residual austenite in quenched rolled 9Kh steels was studied. The specimens were 30 mm long, 4 mm in diameter, and contained 0.88% C and 1.52% Cr. Four sets of experiments were performed. In all of them the initial temperature of the specimen was 850-900C, but cooling was carried out at different rates by using an oil bath at various temperatures. Theoretical predictions for relative quenching deformations gave values 3 to 6 times higher than those measured experimentally ($\epsilon_{\rm max} = 9$ to 10×10^{-14}). Analysis indicates that this discrepancy is caused primarily by the Cord 1/2

tile i samma s

The second secon			<i>i.</i> 1.		
•					
			•		
APLO39602			•		
presence of residual ausresponsible for an incomequal to 10 ⁻¹ to 5 x 10 ⁻¹	plete soluti	on of caroon in	austenite.	win au amount	
to 80-90C temperatures. experiments was observed	The lowest	structural defo	rmation within	n the scope of nce of increase	these d
self-annealing processes art. has: 3 formulas an	and of a ce	rtain amount of	residual aus	tenites). Orig.	
4					
ASSOCIATION: Kuyby*shev	skiy aviatsi	onny#y institut	(Knapaspea y	viation Institu	te)
SUBMITTED: 11Mar63	DATE A	ica: 19Jun64		BNCL:	00
				CONTRACT BUILDING CO. CO.	
	170 PM	. cort 011		Mereo.	
SUB CODE: MM	NO REF	sov: Oll		OTHER:	000
	no rei	SON: OTT		OMER	000
	no rei	sov: Oll		OTHER	000
	no rei	sov: oli		OTHER	000

ARTONIK, M.T., elektrosvarshchik; CHAYKA, V., redektor; TRUKHAHOVA, A., tekhnicheskiy redaktor

[Efficient methods in electric welding] Proisvoditel'nye metody v elektrosvarks. Minsk, Gos. isd-vo BSSR, 1955. 35 p. (MLRA 10:1)

1. Minskiy traktornyy savod (for Antonik) (Blectric welding)

CHAYKA V.A.; MEL'HIKOV,G., redaktor; TRUKHANOVA,A., tekhnicheskiy redaktor

[Principles of manual electric welding] Osnovy ruchnoi dugovoi elektrosvarki. Minsk, Gos.izd-vo BSSR, Red. nauchno-tekhn. lit-ry, 1955. 93 p. (MIRA 9:3)

CHAYKA, V. A.

CHAYKA, V. A.: "Investigation of the plastic properties of steel in the temperature ran e close to the melting point, using contact heating". Minsk, 1955. Min Higher Education USSR. Belorussian Polytechnic Inst imeni I. V. Stalin. (Dissertations for the degree of Candidate of Technical Science.)

SO: Knizhnava Letopis' No. 50 10 December 1955. Moscow.

25(1)

PHASE I BOOK EXPLOITATION SOV/3359

Chayka, V.A.

Osnovy kontaktnoy svarki i elektronagreva (Fundamentals of Resistance Welding and Electric Heating) Minsk, Gos. izd-vo BSSR, 1958. 76 p. (Series: Bibliotechka rabochego mashinostroitelya). 3,000 copies printed.

Ed.: F. Kashtanov; Tech. Ed.: N. Stepanova.

PURPOSE: This booklet is intended for welders working with electric resistance welding machinery.

COVERAGE: The author discusses the principles of electric resistance welding and electric heating. The technique and particularities of various types of resistance welding are described. Welding equipment and adjustments are outlined. Descriptions are illustrated with drawings and tables. Safety rules to be followed in welding jobs are provided. No personalities are mentioned. There are 6 references, all Soviet.

TABLE OF CONTENTS: Card 1/3

Fundamentals of Resistance Welding (Cont.) SOV/3359	
Introduction	3
Electrotechnical and Thermal Principles of Resistance Welding and Electric Heating General principles of electric heating Essentials of spot resistance welding Special aspects of roller welding Butt welding procedures Special aspects of electric heating	6 6 9 14 15
Equipment for Resistance Welding and Electric Heating Main assemblies of resistance welding machines Construction and characteristics of machines for butt welding Construction and characteristics of spot welding machines Machines for roller welding Other resistance welding machines	21 21 32 40 49 52
Resistance Welding Techniques Spot welding technique Technique of roller welding Butt welding technique	54 56 68 71
Card 2/3	•

the control of the co	7/3359		
Technique of electric heating Adjustments for welding	75 76		
Basic Rules of Safety	78		
Bibliography	79		
AVAILABLE: Library of Congress (TK 4660 .C 44)	,,		
Card 3/3	VK/mg 4-26-60		

BEL'SKIY, Ye.I., dots., kand. tekhn. nauk; DMITROVICH, A.M., dots., kand. tekhn. nauk; INTYAKOV, N.G., dots., kand. tekhn. nauk; KAZACHENOK, V.I., dots., kand. tekhn. nauk; CHAYKA, V.A., dots., kand. tekhn. nauk; BOBRYAKOV, G.I., kand. tekhn. nauk, retsenzent; KHUDOKORNOV, D.N., kand. tekhn. nauk, retsenzent

[Technology of the hot-working of metals] Tekhnologiia goriachei obrabotki metallov. [By] E.I.Bel'skii i dr. Minsk, Izd-vo M-va vysshego, srednego spetsial'nogo i professional'nogo obrazovaniin BSSR, 1962. 295 p. (MIRA 15:10)

1. Nauchno-issledovatel'skiy takhnologicheskiy institut avto-mobil'noy promyshlennosti, Minskiy filial (for Bobryakov, Khudokormov).

(Forging) (Founding) (Welding)

CHAYKA Vladimir Antonovich, kand. tekhn. nauk; ANTONIK, Mikhail Terent'yevich, elektrosvarshchik; KASHTANOV, F., red.

[Highly efficient build-up welding with a manually operated arc] Vysokoproizvoditel'naia ruchmaia dugovaia naplavka.
Minsk, Gosizdat BSSR, 1963. 18 p. (MIRA 18:2)

SOURCE CODE: UR/0169/66/000/005/D017/D017 EWT(1) L 46010-66 ACC NR AR6029454 AUTHOR: Andreyeva, R. I.; Gdalevskaya, Ts. M.; Lositskaya, Ye. P.; Klitochenko, T. I.; Marchenko, A. P.; Razumenko, G. F.; Sokolova, N. TITLE: Compilation of composite seismic maps of the southeastern part of the Chavka, V. G. Dnepr-Donets basin SOURCE: Ref. zh. Geofizika, Abs. 5D115 REF SOURCE: Tr. Ukr. n. -i. geologorazved. in-t, vyp. 14, 1965, 132-139 TOPIC TAGS: Dnepr basin seismic map, Donets basin seismic map ABSTRACT: A second interpretation is made of seismic data obtained for the southeastern part of the Dnepr-Donets basin, using supplementary data obtained in drillings. Structural maps to the scale of 1:50,000 and 1:100,000 are plotted for four horizons, from the Cenomanian to the Lower Permian. Iso-pachous line maps, plotted on the basis of data obtained in seismic exploration, are also discussed. A detailed analysis is made of the tectonic structure of the Upper Paleozoic, Mesozoic, and Cenozoic stages on the basis of the above-mentioned UDC: 550.834 **1/2**